



DataRoute voice Wireless Router



The TelecomFM DataRoute voice provides an all-in-one wireless solution for voice and high speed data.

Connection to the internet is provided via either the built-in 3G HSPA wireless module (offering speeds of up to 7.2Mbps downstream and 5.76Mbps upstream) or the built-in ADSL2+ modem. The 3G module can be used as an automatic failover when the ADSL connection is unavailable.

High quality voice is available by connection to a standard analogue POTS phone or to the trunk port of a PBX and calls may be made via the UMTS/GSM network or by using VoIP (SIP) via either of the data connections.

PC's and other networked devices can be connected via the 4 Ethernet ports and by utilising the built-in 802.11n Wi-Fi access point which offers bandwidth of up to 300Mbps.

Dealer's Stamp

Wireless Module

Bands	UMTS 850 / 900 / 1900 / 2100 MHz GSM 850 / 900 / 1800 / 1900 MHz
Transmit Power	Class 3 (0.25W) for UMTS Class E2 for EDGE Class 4 (2W) for GSM 850 / 900 MHz Class 1 (1W) for GSM 1800 / 1900 MHz
Max. Data Rates	HSDPA 7.2Mbps HSUPA 5.76Mbps UMTS 384kbps EDGE 237kbps GPRS 85.6kbps

Features Overview

Built-in 3G HSDPA / HSUPA Wireless Module
802.11n Wi-Fi Access Point
ADSL2/2+ Modem
Automatic failover from ADSL to 3G
Supports TR-069 Remote Management
DHCP Server
Firewall with SPI (Stateful Packet Inspection)
VPN Support
Port Forwarding (Supports DMZ)
Web based management
QoS

Wi-Fi Access Point

Compliance	IEEE 802.11 b/g/n
Security	WEP 64/128/256 bits WPA / WPA2
RF power	20dBm
Transmit Power	802.11b: 16+/-1.5dBm 802.11g: 14+/-1.5dBm 802.11n: HT20 16+/-1.5dBm; HT40 14+/-1.5dBm
Antenna	2T2R MIMO mode (2 transmitter, 2 receiver) External antenna with 2dBi gain Internal antenna with 4dBi gain

Physical Specification

Height	145 mm
Width	170 mm
Depth	35 mm

Ethernet Interface

Compliance	IEEE 802.3
Ports	4 x 10/100M Auto MDI-X

Environmental

Power Supply	100 ~ 240V 50/60Hz
Operating Temp	0 ~ 50°C
Storage Temp	-40 ~ 85°C

DSL Standards

ANSI T1.413 issue 2 compliant
ITU-T G.992.1 (G.DMT) compliant
ITU-T G.992 (G.lite) compliant
ITU-T G.992.3/4 (ADSL2) compliant
ITU-T G.992.5 (ADSL2+) along with Annex A and M

For further information on this and other TelecomFM products and services, please contact TelecomFM

Tel : +44 (0)1753 745000 ~ Fax : +44 (0)1753 745505

E-mail : mail@telecomfm.co.uk ~ web : <http://www.telecomfm.co.uk>

All information is correct at the time of going to print. TelecomFM reserves the right to change any information without notice.