# i-MO 540 Series Bonding Router





### Connectivity wherever & whenever you need it...

The i-MO 540 multichannel router appliance is ideal for providing all the communication and storage requirements for small or medium branch offices or temporary locations. In addition to providing a highly resilient high performance connection to the internet or corporate LAN, the i-MO 540 can optionally be upgraded with:

- VOIP PABX to provide all the voice telephone services
- ♦ 2 x 750GB hard drives and optional NAS software module to provide shared folders and file storage

As standard the appliance is equipped with 6 x GBit Ethernet ports which can individually be configured as WAN or LAN ports.

Optionally the appliance can be upgraded with up to 3 x LTE (4G) or UMTS (3G) cellular modems and up to 6 x network SIMs. If equipped with more SIMs than cellular modems the intelligent i-MO firmware will select the SIM to use based upon network availability or bandwidth allowance.

The appliance can also be upgraded with:

- 4 x 10/100 Fast Ethernet ports giving a total of 10 Ethernet ports that can individually be configured as WAN or LAN ports
- ♦ Up to 2 x High Performance ADSL Interfaces
- ◆ WiFi access point (802.11 b/g/n)

The Administrative Web Interface easily allows the appliance to be configured for link-failover (e.g. from WAN to cellular) in addition to link aggregation to increase performance.

i-MO 540 Series	
i-MO Firmware with	Bandwidth Aggregation Cellular SIM management Intelligent Failover Session Persistence
WAN	DHCP Client Static IP WAN Link Health Check
LAN	Multiple LAN subnets supported DHCP Server DHCP Reservation
VPN	Up to 5 concurrent VPN Tunnels (incoming and outgoing)  IPSEC  Site-to-Site mode  Ciphers: AES and 3DES  Hashes: MD5 and SHA1  Pre-shared Key  NAT-Traversal  Dead Peer Detection
Firewall	Stateful firewall Multiple zones: WAN, DMZ, LAN Multi NAT IP Forwarding Port Forwarding
Advanced QOS	Bandwidth Reservation Application Prioritization
Device Management	Web Administrative Interface Export / Import Configuration

## i-MO 540 Series **Bonding Router**





Technical Specifications	540
Format	2U Rack Mountable / Desktop
Dimensions (WxHxD)	435 x 242 x 92 mm
Weight	4.5 Kg
Mounting	Rack mount option
Status	Intelligent LCD status panel
Embedded Modems	3 x internal slots for LTE/UMTS modules
Cellular Data SIMS	6
Antenna Connectors	5 x SMA
LAN / WAN Interface	6 Gigabit Ethernet ports that individually configurable for WAN or LAN function. LAN ports can be bridged together to act as a switch.
Management Port	RS232 serial console
Power Input	100V - 240V AC, 50-60 Hz
Power Supply	External AC Adapter 100V – 240V / DC Output 12V 5A
Max Power Consumption	50W
Operating Temperature	o°C to ~45°C
Storage	-20°C to +60°C
Humidity	o% to 80% (non-condensing)
СРИ	Intel Atom D525 1.8GHz Dual Core 1M cache
Memory	1GB DDR3 1333MHz
Storage	up to 128GB internal flash storage
Expansion	4 Fast Ethernet Ports - individually configurable for WAN or LAN function Up to 2 x 750GB HD Up to 2 x High Performance ADSL Interfaces G.992.1 (G.DMT), G.922.2 (G. Lite) & G.992 Annex A (ADSL over POTS)
WiFi WLAN Access Point	802.11 b/g/n
Operating Frequency	2.412 ~ 2.472GHz, 2.484GHz
Max Power Output	17dbm ± 2dbm

### **Features**

### Software

i-MO Firmware with: OptiBond Advanced Bandwidth Technology Cellular SIM management Intelligent Failover Session Persistence

### **Device Management**

Web Administrative Interface Export / Import Configuration Command Line Interface

### WAN

**DHCP** Client Static IP WAN Link Health Check

Multiple LAN subnets supported **DHCP Server DHCP** Reservation **DNS Server** 

### WLAN

802.11 b/g/n Access Point

### VPN

Up to 5 concurrent VPN Tunnels (incoming and outgoing) IPsec VPN Site-to-Site mode Ciphers: AES and 3DES Hashes: MD5 and SHA1 Pre-shared Key **NAT-Traversal Dead Peer Detection** 

### Firewall

Stateful firewall with support for PPTP, FTP,SIP,H.323 Multiple zones: WAN, DMZ, LAN Multi NAT IP Forwarding Port Forwarding

### **Advanced QoS**

Bandwidth Reservation **Application Prioritization** 























### **UK Head Office:**

e-mail: imo@ems-uk.com

### **SE Asia Distributor:**

e-mail: sales@bninfotech.com.sg

